

# EASTBOUND SPEEDWAY – AVONDALE, NL

## SPORTSMAN DIVISION RULES – 2021   \*\*updated February 10, 2021

**NOTE:** No equipment shall be considered as having been approved by reason of having passed through inspection unobserved. The technical director shall determine as to whether any type of construction, design, or interpretation of any rule shall be accepted.

Eastbound Speedway reserves the right to update, modify, add, or delete rules at any time in the interest of providing parity to all competitors. Additional requirements may be made via official entry registration, technical bulletin, or meeting announcement, which automatically amends specifications within. All changes will be posted.

Consequences for not following all technical specifications as listed below will be at the discretion of the race officials. Infraction of rules pertaining to engines, chassis design, and safety considerations may result in disqualification and possibly from future events, at the discretion of track officials.

### 1.    **CAR MODELS**

- 1.1    NORTH AMERICAN REAR WHEEL DRIVE CARS WITH FRONT ENGINES AND FULL FRAMES (EXCLUDING MOPAR) ALLOWED.
- 1.2    NO MUSTANGS, BARRACUDAS, CHALLENGERS, OR SIMILARLY DESIGNED CARS ALLOWED
- 1.3    108” **MINIMUM** WHEELBASE (FACTORY SPECIFICATIONS) WITH NOT MORE THAN 1” DIFFERENCE (PLUS OR MINUS) FROM SIDE TO SIDE. **EXAMPLE: LEFT: 108”...RIGHT: 109” MAX**
- 1.4    JOHNSON FRONT AND REAR CLIPS, MID SECTIONS AND CAGES ARE ALLOWED
- 1.5    ANY METRIC CHASSIS, CAMARO FRONT CLIP, OR OEM AFTERMARKET 2X4 OR 2X3 FRONT CLIP ARE ALLOWED (SEE WEIGHT RULE)
- 1.6    MUST HAVE STOCK LOCATIONS FOR ALL BOLT ON PARTS AND CROSSMEMBERS
- 1.7    FABRICATED REAR CLIPS AND KICK UPS ALLOWED.
- 1.8    PERIMETER CHASSIS ONLY, STRAIGHT RAIL CHASSIS NOT PERMITTED

### 2.    **ROLL CAGES**

- 2.1    MATERIAL TO BE USED MUST BE .090 (MINIMUM WALL) MILD STEEL TUBING. LOW CARBON MILD STEEL TUBING RECOMMENDED. OTHER MATERIALS ARE SUBJECT TO PRIOR APPROVAL

- 2.2 NO IRON PIPE ALLOWED. NO BRAZING OR SOLDERING ALLOWED.
- 2.3 SUPPORTS MUST BE FRAME MOUNTED IN AT LEAST SIX (6) PLACES (FOUR UPRIGHT PIPES AND TWO BRACES TOWARDS THE REAR)
- 2.4 NO FRONT CAGE MOUNTS ALLOWED
- 2.5 REAR CAGE MOUNTS MAY BE ON THE OUTSIDE OF FRAME ONLY, NOT BEYOND THE OUTSIDE EDGE OF THE FRAME
- 2.6 ALL CARS ARE REQUIRED TO HAVE A 4-POINT OR MAIN STRUCTURE OF ROLL CAGE
- 2.7 THE BOTTOM OF THE ROLL CAGE MUST REMAIN CENTRED ON THE DRIVE LINE PLUS OR MINUS 1.5"
- 2.8 MINIMUM LENGTH OF LEFT SIDE DOOR BARS IS 42"
- 2.9 MAIN CAGE STRUCTURE AND DOOR BARS MINIMUM 1.66" O.D.
- 2.10 TOTAL HEIGHT OF ROLL CAGE TO BE 39" (MINIMUM) FROM BOTTOM OF FRAME
- 2.11 HALO TO BE NO LESS THAN 1" LOWER AT ANY POINT
- 2.12 WIDTH OF HALO TO BE NO LESS THAN 32" OUTSIDE TO OUTSIDE OF TUBING.
- 2.13 DASH BAR REQUIRED, ALONG WITH AN X-TYPE MEMBER ACROSS AND BEHIND DRIVER
- 2.14 RIGHT SIDE-BARS (INSTEAD OF DOOR BARS) MUST BE NO FURTHER IN TOWARD DRIVELINE THAN AN IMAGINARY LINE CONNECTING THE FRONT CLIP TO THE REAR CLIP (AT KICK OUTS)
- 2.15 HALO MUST BE FURTHER BRACED TO RIGHT SIDEBARS. ONE PIECE OF TUBING MUST RUN DIAGONALLY OR PERPENDICULAR BETWEEN HALO IN TOP OF CAGE
- 2.16 FOUR CURVED HORIZONTAL DOOR BARS ON DRIVER'S SIDE WITH MINIMUM OF EIGHT INCHES TO EDGE OF SEAT FROM INSIDE OF DOOR BARS REQUIRED
- 2.17 DOOR BARS MUST BE TIED TOGETHER WITH VERTICAL BARS AND WELDED TO THE FRAME IN AT LEAST TWO ADDITIONAL PLACES.
- 2.18 MINIMUM HEIGHT OF DOOR BARS 22.5" FROM BOTTOM OF FRAME
- 2.19 A SO-CALLED "PETTY BAR" MUST RUN FROM CENTRE OF CAGE (REAR) TO UPPER RIGHT FRONT HALO ON ANY HALOS OVER 40" WIDE
- 2.20 CARS THAT DO NOT HAVE RIGHT SIDE DOOR BARS OUT TO THE BODY (66" PERIMETER CAGE) THERE MUST BE ONE BAR (1.50" O.D., .090 THICKNESS, MINIMUM) NOT LESS THAN THE LENGTH OF THE FRAME RAIL AND A MINIMUM OF 12" ABOVE THE FRAME, RUNNING FRONT TO REAR WITH A MINIMUM OF TWO HORIZONTAL BRACES, OFF THE RIGHT SIDE BARS WITH A MINIMUM OF 66" OUTSIDE TO OUTSIDE FROM THE DRIVER'S

- SIDE DOOR BARS AND A MINIMUM OF TWO ADDITIONAL BRACES TYING THE MAIN BAR BACK INTO THE FRAME.
- 2.21 NO BRACE BARS FORWARD OF CAGE MAY BE HIGHER THAN STOCK HOOD HEIGHT
  - 2.22 A FORWARD BRACE OFF THE LEFT FRONT UPRIGHT FOR FOOT PROTECTION IS MANDATORY. A PIECE OF PLATE STEEL OF AT LEAST 1/16" THICKNESS SHOULD BE WELDED TO THE OUTSIDE OF THE DOOR AND FOOT BARS ON THE DRIVER'S SIDE
  - 2.23 ANY BRACING NOT ATTACHED TO ORIGINAL FRAME IS SUBJECT TO APPROVAL OF OFFICIALS.

### 3. ALUMINUM

- 3.1 NO ALUMINIUM OR EXOTIC METAL WHEELS, HUBS, HATS, ROTORS, CALIPERS, "A" FRAMES, SPINDLES, OR ANY OTHER SUSPENSION OR REAR END PARTS ARE ALLOWED
- 3.2 NO ALUMINIUM DRIVE SHAFTS, BRACKETS, FLYWHEELS, CYLINDER HEADS OR HARMONIC BALANCERS.

### 4. SEAT

- 4.1 ALUMINIUM RACING SEATS ARE MANDATORY
- 4.2 NO FIBREGLASS SEATS
- 4.3 SEAT BOTTOM AND BACK MUST BE BOLTED TO FRAME AND CAGE
- 4.4 SEAT BELTS SHOULD BE FASTENED TO THE ROLL CAGE AT SHOULDER HEIGHT. (FULL CONTAINMENT RECOMMENDED)
- 4.5 ON KIT-BODIED CARS, THE SEAT MUST BE POSITIONED SO THAT THE BACKREST IS NO MORE THAN 70% OF THE WHEELBASE (FACTORY SPECIFICATION) FROM THE FRONT SPINDLE (MEASURED FROM THE BACK OF THE BOTTOM OF SEAT)
- 4.6 BACK OF THE SEAT NEAR SHOULDER HEIGHT AREA TO CENTRE OF REAR HOUSING NO LESS THAN 25"
- 4.7 MINIMUM 8" REQUIRED BETWEEN DRIVER'S DOOR BARS AND SEAT
- 4.8 THE BOTTOM OF THE SEAT AND ALL SEAT MOUNTS AND FRAMES MUST BE ABOVE THE BOTTOM OF THE FRAME.

## 5. RADIATOR

- 5.1 ONE RADIATOR ONLY AND IT MUST BE MOUNTED IN FRONT LOCATION
- 5.2 NO REAR MOUNTED RADIATORS
- 5.3 IF A MINIMUM FOUR BLADE STEEL FAN (THAT IS OPERATING AND HAS ALL BLADES FULL AND COMPLETE) IS USED, AN ADDITIONAL ELECTRIC FAN IS OKAY
- 5.4 NO ANTIFREEZE OR OTHER COOLING AGENTS PERMITTED. **WATER ONLY**
- 5.5 RADIATOR OVERFLOW MUST EXIT WITHIN THE ENGINE COMPARTMENT (OVERFLOW CAN) OR ONTO THE RIGHT LOWER CORNER OF THE WINDSHIELD
- 5.6 HOOD MUST COVER RADIATOR WITHOUT MODIFICATION.

## 6. IGNITION

**(NEW 2021 ITEMS # 6.5, #6.6, #6.7, #6.8 and #6.9)**

- 6.1 CAR MUST BE SELF-STARTING AND IGNITION "OFF" SWITCH MUST BE MOUNTED NEAR THE CENTERLINE OF THE CAR AND CLEARLY LABELLED "IGNITION OFF" IN SUCH A MANNER THAT THE ENGINE CAN BE TURNED OFF FROM EITHER SIDE OF THE CAR IN THE EVENT OF AN EMERGENCY.
- 6.2 BATTERY OPERATED IGNITIONS ONLY. NO MAGS
- 6.3 ONLY STOCK HEI TYPE DISTRIBUTOR AND STOCK TYPE COIL PERMITTED
- 6.4 STOCK SINGLE-POINT DISTRIBUTOR AND STOCK TYPE COIL PERMITTED. NO DUAL POINTS
- 6.5 A **6ALN** MSD BOX IS **MANDATORY** FOR ALL SPORTSMAN CARS, ALL ENGINES, CRATE INCLUDED, NO EXCEPTIONS
- 6.6 MSD 6ALN MUST BE WIRED INTO THE SYSTEM WITH THE ORIGINAL PLUG SUPPLIED WITH THE UNIT. WIRING PLUG CANNOT BE COVERED OR HIDDEN FROM VIEW AND NO ADDITIONAL WIRES MAY BE WIRED TO OR FROM THE UNIT
- 6.7 **MAX 5800RPM CHIP (PLUG IN STYLE)**
- 6.8 NO DIGITAL BOXES WITH DIAL CONTROLS OR EXTERNAL REV LIMITER SELECTOR SWITCHES ALLOWED
- 6.9 ONLY ONE MSD BOX PERMITTED
- 6.10 MSD BOXES MUST BE MOUNTED **OUT OF THE DRIVER'S REACH** WHILE BELTED IN

## 7. GAUGES

- 7.1 INSTRUMENTS – OIL PRESSURE AND HEAT GAUGES MANDATORY

**8. STARTER/BATTERY**

- 8.1 BATTERY MUST BE ANCHORED SECURELY AND SEPARATED FROM DRIVER'S COMPARTMENT BY A FIREWALL.
- 8.2 ONE 12 VOLT BATTERY ONLY.
- 8.3 BATTERY DISCONNECT SWITCH IS MANDATORY AND MUST BE CLEARLY MARKED AND ACCESSIBLE TO SAFETY CREW.
- 8.4 STARTER MUST BE IN STOCK POSITION, OEM DESIGN AND FUNCTIONAL

**9. ENGINE LOCATION**

- 9.1 ALL MOTORS MUST BE CENTERED BETWEEN FRAME RAILS. THE DISTANCE FROM THE BACK OF THE BLOCK TO THE CENTER OF THE REAR AXLE HOUSING CANNOT BE LESS THAN 84% OF THE WHEELBASE. MAXIMUM 2" SETBACK BEYOND 84% ALLOWED ON FORD AND MOPAR, EXCEPT MOPAR WITH G.M. CHASSIS. MINIMUM CRANKSHAFT HEIGHT WILL BE THE FRAME HEIGHT PLUS SEVEN INCHES

**10. SUSPENSION**

**(NEW 2021 ITEMS #10.18, #10.19)**

- 10.1 ALL COIL SPRINGS MUST BE AT LEAST 4 1/2 INCHES OUTSIDE DIAMETER
- 10.2 REAR COIL SPRING POCKETS CAN BE REINFORCED OR EXTENDED TO ALLOW FOR A LONGER SPRING
- 10.3 NO COIL-OVER SHOCKS ALLOWED
- 10.4 JACKING BOLTS ARE ALLOWED
- 10.5 ANY SWAY BAR MUST BE FACTORY STOCK OEM
- 10.6 FRONT SWAY BAR MAY HAVE ADJUSTABLE LINKS.
- 10.7 STOCK FRONT CROSS MEMBER MUST REMAIN WITH THE FOLLOWING ALTERATIONS (ALL NOTCHES MUST BE BOXED IN)
- 10.8 NO RACK AND PINION STEERING – CONVENTIONAL STEERING ONLY
- 10.9 STEERING COLUMN MUST HAVE A COLLAPSIBLE LINK AND PADDED STEERING WHEEL.
- 10.10 NO EXCESSIVE LIGHTENING OR DRILLING. FRONT AND REAR SUSPENSION AND STEERING COMPONENTS MUST BE UNCUT AND OEM FOR THAT FRAME
- 10.11 NO FABRICATED SPINDLES. SPINDLE SAVERS ARE ALLOWED
- 10.12 BOTTOM 'A' FRAMES CANNOT BE ALTERED DRILLED OR MOVED AND MUST BE STOCK OEM FOR FRAME USED

- 10.13 STOCK UPPER 'A' FRAMES MAY BE HULLED FOR SCREW JACK CLEARANCE ONLY
- 10.14 METRIC CHASSIS MAY USE EITHER A 0.5" OEM OFFSET SHAFT OR A MAXIMUM 3.25" OEM BOLT (GRADE 8 BOLT OR BETTER WITH OEM THREAD) ON UPPER "A" FRAMES ONLY
- 10.15 STEEL BUSHINGS ARE ALLOWED IN STOCK UPPER "A" FRAMES. NO REINFORCING. NO CUTTING, NOTCHING AND/OR RE-WELDING OF CONTROL ARM SIDES.
- 10.16 HEX TUBE ARMS AND HEIM END JOINTS PERMITTED
- 10.17 ALL SUSPENSION AND STEERING COMPONENTS MUST BE STOCK LENGTH AND MOUNTED IN STOCK LOCATION UNLESS OTHERWISE INDICATED (E. G. SHOCK MOUNTS MAY BE MOVED).
- 10.18 LEFT FRONT WHEEL MAXIMUM CAMBER MAY BE 4.0 DEGREES POSITIVE OR NEGATIVE (**NO TOLERANCE**)
- 10.19 RIGHT FRONT WHEEL MAXIMUM CAMBER MAY BE 6.0 DEGREES POSITIVE OR NEGATIVE (**NO TOLERANCE**)
- 10.20 BUSHINGS: ALL SUSPENSION BUSHINGS WILL BE RUBBER, STEEL OR NEOPRENE ONLY.

## 11. **SHOCKS**

- 11.1 ONE STEEL BODY SHOCK PER WHEEL ONLY FOR A TOTAL OF FOUR SHOCKS PER CAR
- 11.2 **AFCO SHOCKS ONLY WITH THE FOLLOWING NUMBERS: 1078, 1275FB, 1276B, 1277FB, 1278FB, 14775FB, 1475FB, 1477FB AND 1478FB. NUMBERS MUST BE READABLE**
- 11.3 NO RESERVOIR TYPE SHOCKS
- 11.4 NO SHOCKS FOR COILOVERS
- 11.5 ID NUMBERS AND MANUFACTURER MUST BE READABLE AND TRACKABLE
- 11.6 NO FIVE-DIGIT (SPLIT VALVE) SHOCKS ALLOWED
- 11.7 NO REMOTE OR RE-BUILDABLE SHOCKS
- 11.8 MAXIMUM \$150.00 PER SHOCK
- 11.9 NO BUMPSTOPS OR PACKERS OF ANY KIND.

## 12. **FRAMES**

**(NEW 2021 ITEMS #12.2, # 12.9)**

- 12.1 FRAMES CAN BE FABRICATED TO ACCOMMODATE OEM OR AFTERMARKET CLIPS
- 12.2 108" **MINIMUM** WHEELBASE (FACTORY SPECIFICATIONS) WITH NOT MORE THAN 1" DIFFERENCE (PLUS OR MINUS) FROM SIDE TO SIDE. **EXAMPLE: LEFT: 108"...RIGHT: 109" MAX**

- 12.3 AFTER MARKET UPPER CONTROL ARMS ALLOWED BUT MUST USE STOCK (OEM) BALL JOINTS
- 12.4 THREE-LINK OR FOUR-LINK REAR SUSPENSION CONFIGURATIONS ALLOWED
- 12.5 ANY THREE OR FOUR POINT HOOK UP MAY BE USED.
- 12.6 LOWER ARMS MUST NOT EXCEED 30" FROM MOUNTING HOLES ON REAR END TO MOUNTED HOLES ON FRAME
- 12.7 SOLID ONE PIECE BARS ONLY IN EITHER APPLICATION
- 12.8 UPPER ARMS MUST NOT EXCEED 30" AND MUST BE SOLID
- 12.9 NO RUBBER BISCUITS ALLOWED
- 12.10 PANHARD BAR MUST BE A ONE PIECE SOLID BAR
- 12.11 HEIM JOINTS ALLOWED.
- 12.12 MAXIMUM TREAD WIDTH (MEASURED OUTSIDE OF ONE WHEEL TO OUTSIDE OPPOSITE WHEEL AT SPINDLE HEIGHT) 78 INCHES.
- 12.13 FRAME CAN HAVE ONE TUBING BRACE FROM RIGHT FRONT CLIP TO RIGHT REAR CLIP, PARALLEL TO SIDE RAIL. NO PART OF ROLL CAGE OR SUSPENSION CAN BE ATTACHED TO THIS BRACE.
- 12.14 FRAME RAILS CAN BE SYMMETRICALLY CROSS-BRACED OR X-BRACED USING TUBING ONLY. ALL BRACING MUST BE NO LOWER THAN THE BOTTOM OF THE FRAME RAILS
- 12.15 FRAME MUST SUPPORT THE ROLL CAGE ON BOTH SIDES.

**13. REAR END**

- 13.1 9" FORD; GM WITH BOLT ON BEARING LOCKS (C-CLIP ELIMINATORS) OR SPOT WELDED CLIPS ARE MANDATORY
- 13.2 LOCKED REAR ENDS ARE ALLOWED
- 13.3 NO TRACTION CONTROL OR SIMILAR DEVICES ARE ALLOWED
- 13.4 NO GUN DRILLED AXLES. REAR END AND ALL SUSPENSION PARTS MUST BE STOCK TYPE AND IN ORIGINAL LOCATION
- 13.5 ONLY UPPER CONTROL ARMS MAY BE RE-DRILLED
- 13.6 REAR OEM/AFTERMARKET TRAILING ARMS MUST REMAIN IN STOCK POSITION ON FRAME AND REAR END HOUSING. NO SLOTTED OR ELONGATED MOUNTING HOLES
- 13.7 ONLY ONE MOUNTING HOLE ALLOWED AT EACH MOUNTING LOCATION.
- 13.8 NO QUICK-CHANGE REAR ENDS
- 13.9 NO DETROIT LOCKERS
- 13.10 NO ALUMINUM CARRIERS OR SPOOLS
- 13.11 REAR END MUST MEASURE THE SAME BETWEEN EACH BRAKE AND THE DRIVE PINION
- 13.12 PICK UP POINTS ON REAR ENDS MUST MEASURE SAME AS STOCK
- 13.13 NO REINFORCING OF ANY KIND ON HOUSING.

**14. GEAR RATIO**

**(NEW 2021 ITEMS #14.1, #14.2)**

- 14.1 THE FINAL DRIVE MAY NOT EXCEED 5:50:1.
- 14.2 CARS NOT USING 1:1 TRANSMISSION OUTPUT WILL BE CALCULATED USING GEARBOX RATIO TIMES DIFFERENTIAL GEARS TO DETERMINE MAXIMUM FINAL DRIVE OF NO MORE THAN 5:50:1 COMBINED

**15. BRAKES**

- 15.1 BRAKES MUST BE OPERATING ON ALL FOUR WHEELS AND MUST LOCK UP FOR INSPECTION
- 15.2 BRAKES MUST BE OEM STYLE ONLY, ONE CALIPER PER WHEEL AND ONE PISTON PER CALIPER
- 15.3 DISC BRAKES WILL BE ALLOWED ON REAR WHEELS, ONE CALIPER AND ONE PISTON PER CALIPER.
- 15.4 PEDALS CAN BE HUNG FROM TOP OR BOTTOM ONLY
- 15.5 MASTER CYLINDER MUST BE LOCATED UNDER HOOD IN STOCK LOCATION (ON FIREWALL, LEFT SIDE OF ENGINE, ABOVE FRAME)
- 15.6 TWO MASTER CYLINDERS ALLOWED
- 15.7 CALIPER BRACKETS MUST BE MOUNTED IN A FIXED POSITION
- 15.8 BRAKE DUCTS OKAY ON FRONT ONLY
- 15.9 ONE ADJUSTMENT PROPORTIONING VALVE OR ONE BIAS VALVE IS ALLOWED
- 15.10 NO DRILLED ROTORS.

**16. TRANSMISSIONS**

- 16.1 ONLY OEM STOCK PRODUCTION THREE SPEED OR FOUR SPEED (STEEL OR ALUMINIUM) TRANSMISSION WILL BE ALLOWED.
- 16.2 NO VARIABLE RATIO TRANSMISSIONS ALLOWED
- 16.3 NO FIVE-SPEED TRANSMISSIONS ALLOWED
- 16.4 TRANSMISSION MUST HAVE ALL FORWARD GEARS WORKING AND ONE GEAR REVERSE, PLUS A NEUTRAL
- 16.5 RATIOS FOR ALL GEARS MUST BE OEM FOR TRANSMISSION USED
- 16.6 ALL VEHICLES MUST START WITHOUT BEING PUSHED OR PULLED (AT DISCRETION OF OFFICIALS).

**17. BELL HOUSING CLUTCH AND FLYWHEEL**

- 17.1 MUST HAVE N.H.R.A. APPROVED STEEL BELL HOUSING
- 17.2 BELL HOUSING SHOULD HAVE AN INSPECTION PLATE. IF THERE IS NO INSPECTION PLATE YOU WILL BE REQUIRED TO REMOVE BELL HOUSING FOR CLUTCH INSPECTION



- 17.3 STOCK STEEL OEM TYPE UNITS ONLY. NO TURNED, DRILLED, (FOR LIGHTNING PURPOSES) ALUMINUM OR SPECIAL FLY WHEEL PARTS PERMITTED.
  - 17.4 NO TRIPLE DISK CLUTCHES, COUPLERS, FLEX PLATES OR AUTOMATIC FLYWHEELS ALLOWED
  - 17.5 MIN FLYWHEEL WEIGHT OF 14 LBS
18. **CRATE ENGINES (602 ONLY)**
- 18.1 SEALED CHEVROLET 602 GM CRATE ENGINE #19258602 (FORMERLY #88958602) IS PERMITTED
  - 18.2 GM CRATE OR BUILT ENGINES MUST BE IDENTIFIED PRIOR TO PRE-RACE TECHNICAL INSPECTION
  - 18.3 MUST BE STOCK SPECS AS PER GM WITH NO MODIFICATIONS. ZERO TOLERANCE ON ALL STOCK SPECS
  - 18.4 602 GM CRATE ENGINE PART # 88958602 OR 19258602 THAT ARE FACTORY SEALED BY GM AND/OR APPROVED BY EASTBOUND SPEEDWAY WILL BE PERMITTED AN OPTIONAL CARBURETOR. APPROVED ENGINES MUST HAVE ALL ORIGINAL GM FACTORY TAMPER PROOF SEALS INSTALLED OR A DOCUMENTED REPAIR APPROVED BY EASTBOUND SPEEDWAY OFFICIALS. SEALED ENGINES MUST PULL A MINIMUM OF 18 INCHES OF VACUUM (NO TOLERANCE) REPAIRED/FRESHENED CRATE ENGINES ONLY, NOT REBUILD WILL HAVE TO MEET SPECIFIC GUIDELINES AS SET BY EASTBOUND SPEEDWAY AND OUTLINED UNDER "WEIGHT". THIS CARBURETOR IS A HOLLEY 80541 THIS UNIT IS TO BE INSTALLED WITH NO MODIFICATIONS "BOX STOCK". THE CARBURETOR WILL BOLT DIRECTLY TO THE INTAKE USING A GASKET ONLY, NO SPACER PLATE WILL BE ALLOWED. THE CARBURETOR SHALL REMAIN AS PRODUCED. ALL REPAIRED/ FRESHENED CRATE ENGINES MUST MEET ORIGINAL SPECIFICATIONS AS PER GM PERFORMANCE. INSPECTIONS MAY INCLUDE, CONFIRMATION OF STOCK ORIGINAL COMPONENTS, GAUGE TESTS (GO/NO GO) AS WELL AS ANY OTHER TESTS TO CONFIRM COMPLIANCE. **(Refer to ASPIRATION #25 for additional information)**
  - 18.5 BUILT ENGINES AND 602 GM CRATE PART # 88958602, 19258602 OPENED OR FRESHENED, MISSING SEALS, MEETING ALL STOCK GM CRATE SPECS, OTHER THAN CAM DURATION AND PULLING LESS THAN 18" VACUUM MUST USE A HOLLEY 500 R4412 ONLY AND HAVE MAXIMUM .390" / .410" CAMSHAFT LIFT **(Refer to ASPIRATION #24 for additional information)**
  - 18.6 ALL ENGINE PACKAGES MUST BE A MAX 9.1 TO 1 COMPRESSION RATIO AS CALCULATED BY OUR TRACK WHISTLER. **9.3 TO 1 WILL BE DEEMED ILLEGAL.** ALL VACUUM TESTS WILL BE AT 900 RPM USING TRACK TECH TOOLS AND RPM GAUGE ONLY

19. **BUILT ENGINE (GM, FORD and MOPAR)**

- 19.1 GENERAL MOTORS: 350 CU. IN. CHEV WITH 4.000" BORE AND 3.480" STROKE
- 19.2 FORD: 351CU. IN. WINDSOR WITH 4.000" BORE AND 3.500" STROKE
- 19.3 MOPAR 360 CU. IN. WITH 4.000" BORE AND 3.578" STROKE
- 19.4 MOPAR 360 CU. IN. PERMITTED IN GM METRIC CHASSIS
- 19.5 .060 OVERBORE PERMITTED, MAXIMUM 365 CUBIC INCHES
- 19.6 NO STROKER ENGINES
- 19.7 NO ROLLER CAMS OR REV KITS ALLOWED
- 19.8 HYDRAULIC LIFTER CAMSHAFT WITH MAXIMUM VALVE LIFT AS FOLLOWS:
  - GM - INTAKE .410, EXHAUST .390
  - FORD - INTAKE .445, EXHAUST .453.
  - MOPAR - INTAKE .410, EXHAUST .410.
- 19.9 VALVE LIFT IS DETERMINED BY MULTIPLYING THE ACTUAL CAMSHAFT LIFT BY THE MAXIMUM ALLOWABLE ROCKER ARM RATIO.
- 19.10 STOCK SIZE HYDRAULIC LIFTERS ONLY (NO MUSHROOM TYPE)
- 19.11 TRW LIFTERS WITH C-CLIPS ARE PERMITTED
- 19.12 NO SOLID, ANTI-PUMP OR RHOADS LIFTERS
- 19.13 VALVES MUST NOT HAVE OVER ZERO LASH CLEARANCE.
- 19.14 MAX COMPRESSION RATIO 9.1 TO 1 - **9.3 TO 1 WILL BE DEEMED ILLEGAL.**

20. **PISTONS AND RODS**

- 20.1 STOCK CAST OR FORGED (DISHED OR FLAT TOP) PISTONS ONLY (OR EQUIVALENT REPLACEMENT)
- 20.2 FOUR VALVE RELIEF PISTONS ARE MANDATORY ON G.M
- 20.3 THE PISTON, RINGS, ROD, END CAP, ROD BOLTS AND BEARINGS WILL WEIGH A MINIMUM OF 1350 GRAMS AS A UNIT
- 20.4 PISTONS CANNOT COME ABOVE BLOCK, DECK HEIGHT OF .005" RECOMMENDED
- 20.5 STOCK CONNECTING RODS (NO 6" GM RODS) AND PRESSED WRIST PINS ONLY
- 20.6 NO FLOATING PISTON PINS
- 20.7 AFTER MARKET CONNECTING ROD BOLTS AND NUTS ARE ALLOWED.

21. **CYLINDER HEADS**

- 21.1 NO VORTEC OR ALUMINUM HEADS ON BUILT ENGINES
- 21.2 ALL CYLINDER HEADS MUST HAVE STOCK INTAKE AND EXHAUST VALVES AND STOCK VALVE SPRING DIMENSIONS - 1.275"
- 21.3 G.M.; 1.437" FORD; 1.5" MOPAR. STOCK REPLACEMENT STAINLESS VALVES PERMITTED

- 21.4 NO SWIRL POLISHED VALVES
- 21.5 NO TITANIUM VALVES
- 21.6 VALVE STEM LENGTH, DIAMETER, AND KEEPER GROUP LOCATION MUST BE STOCK
- 21.7 STOCK STEEL RETAINERS MUST BE USED
- 21.8 NO ANGEL MILLING, PORT MATCHING, POLISHING OR BLUEPRINTING IS ALLOWED
- 21.9 HEADS MAY BE MILLED FOR STRAIGHTNESS ONLY
- 21.10 STOCK ROCKER ARMS (OR EQUIVALENT REPLACEMENT) WITH STOCK RATIOS ONLY (GM 1.5, FORD 1.6, MOPAR 1.5)
- 21.11 JAM NUTS ARE PERMITTED
- 21.12 NO POLY LOCKS
- 21.13 SCREW-IN STUDS AND GUIDE PLATES ARE PERMITTED
- 21.14 NO ADDITIONAL VALVE SPRINGS ALLOWED
- 21.15 ANY EXTRA DECK CLEARANCE OR HEAD GASKET THICKNESS CAN BE APPLIED TO THE COMBUSTION CHAMBER USING ONE-THOUSANDTH EQUALS 206 CC'S.
- 21.16 ALL CYLINDER HEADS MUST BE CAST IRON, OEM (NUMBERS READABLE) OPEN CHAMBERED SMOG HEADS WITH SPECIFICATIONS AS FOLLOWS:

#### **GM HEADS**

- MAXIMUM INTAKE DIAMETER 1.94", MAXIMUM EXHAUST DIAMETER 1.5"
- MINIMUM COMBUSTION CHAMBER VOLUME 76CC
- MINIMUM COMBINED DECK CLEARANCE PLUS HEAD GASKET THICKNESS .050"
- MAXIMUM INTAKE RUNNER VOLUME 160 CC
- MAXIMUM EXHAUST RUNNER VOLUME 60 CC.

#### **FORD HEADS**

- MAXIMUM INTAKE DIAMETER 1.84", MAXIMUM EXHAUST DIAMETER 1.55"
- MINIMUM COMBINED DECK CLEARANCE PLUS HEAD GASKET THICKNESS .080" FOR ALL HEADS.
- WITH MINIMUM COMBUSTION CHAMBER VOLUME OF 69 CC., AND MAXIMUM INTAKE RUNNER VOLUME OF 125 CC., A FLAT TOP PISTON MUST BE USED
- WITH MINIMUM COMBUSTION CHAMBER VOLUME OF 60 CC., AND MAXIMUM INTAKE RUNNER VOLUME OF 140 CC., A DISHED PISTON WITH .120" CUP MUST BE USED

#### **MOPAR HEADS**

- MAXIMUM INTAKE DIAMETER 1.88", MAXIMUM EXHAUST DIAMETER 1.6"

- MINIMUM COMBUSTION CHAMBER VOLUME 68 CC
- MINIMUM COMBINED DECK CLEARANCE PLUS HEAD GASKET THICKNESS, WITH A FLAT TOP PISTON .120"
- MAXIMUM INTAKE RUNNER VOLUME 162 CC
- MAXIMUM EXHAUST RUNNER VOLUME 72 CC
- THE FOLLOWING HEADS ARE APPROVED: 3169974, 3671587, 3751357, 3751857, 3769596, 4027596, AND 4448308.  
(NOTE: 4448308 MAXIMUM 162 CC. INTAKE RUNNERS AND 62 CC. EXHAUST RUNNERS IS ALLOWED. A 50 LB. WEIGHT PENALTY WILL APPLY SUBJECT TO REVIEW BY OFFICIALS.)

**22. INTAKE MANIFOLD**

- 22.1 STOCK CAST IRON OR ALUMINUM GM 12366573 OR PERFORMANCE PRODUCTS 52028 ONLY.

**23. CRANKSHAFT**

- 23.1 ONLY STANDARD STEEL OR CAST PRODUCTION DESIGN  
 23.2 NO LIGHTWEIGHT CRANKS  
 23.3 STROKE MAY NOT BE INCREASED OR DECREASED.  
 23.4 NO LIGHTENING OR KNIFE EDGING.  
 23.5 NO ALUMINUM HARMONIC BALANCER, HARMONIC BALANCER MUST BE STOCK FOR OEM ENGINE

**24. ASPIRATION (2BBL. CARBURETOR 500 CFM HOLLEY #R4412)**

**(NEW 2021 ITEMS #24.2, #24.3, #24.4, #24.7)**

- 24.1 ONE R4412-500 C.F.M. HOLLEY FACTORY STOCK PRODUCED TWO BARREL CARBURETOR ONLY.  
 24.2 A FOUR BARREL TO TWO BARREL ADAPTER, MAXIMUM 1 1/8" THICK MAY BE USED  
 24.3 HOLES MUST BE REMAIN PARALLEL TOP TO BOTTOM, NO RE-WORKING OF ADAPTER OF ANY KIND  
 24.4 THE ONLY CHANGES ALLOWED ARE JETS; POWER VALVE AND REMOVAL OF CHOKE PARTS.  
 24.5 MANDATORY TWO THROTTLE RETURN SPRINGS IN OPPOSITE DIRECTIONS.  
 24.6 SERIAL NUMBERS MUST BE READABLE  
 24.7 NO CARBURETOR HATS ALLOWED.  
 24.8 AIR CLEANERS ARE MANDATORY.  
 24.9 AN ACCELERATOR TOE BAR MANDATORY.  
 24.10 NO RAM AIR SYSTEMS.  
 24.11 A QUICK-CHANGE JET KIT (PART #3425 FLOAT BOWL) MAY BE USED.  
 24.12 THE VACUUM PORT @ THE BASE OF THE CARB MAY PLUG BY TAPING THE HOLE AND REPLACING IT WITH A THREADED PLUG.

- 24.13 NO PERFORMANCE BUILT, SPECIALITY BUILT OR MODIFIED CARBURETORS OR THEIR COMPONENTS
- 24.14 ALL AIR ENTERING THE ENGINE FOR COMBUSTION PURPOSES MUST ENTER THROUGH THE AIR HORN OF THE CARBURETOR
- 24.15 METERING BLOCK MUST HAVE THE FOLLOWING ID# STAMPED ON IT. FACTORY STOCK #5924 OR #5925. THE #10570 WILL APPEAR ON REPLACEMENT OR SERVICE METERING BLOCKS. METERING BLOCK POWER VALVE CHANNEL RESTRICTION PORTS (2 HOLES BEHIND THE POWER VALVE) MAXIMUM .0635" METERING BLOCK IDLE FEED RESTRICTION PORTS (2 HOLES) MAXIMUM .035" METERING BLOCK MAIN PASSAGE TO DISCHARGE NOZZLE (2 HOLES) MAXIMUM .141"

**25. ASPIRATION (4BBL. CARBURETOR 650 CFM 4150 HOLLEY #80541-1. )**

**(NEW 2021 ITEMS #25.3, #25.7, #25.8, #25.12 AND ADDITIONAL NOTE)**

- 25.1 602 GM CRATE ENGINE PART # 88958602 OR 19258602 THAT ARE FACTORY SEALED BY GM AND/OR APPROVED BY EASTBOUND INTERNATIONAL SPEEDWAY WILL BE PERMITTED AN OPTIONAL 4BBL CARBURETOR
- 25.2 APPROVED ENGINES MUST HAVE ALL ORIGINAL GM FACTORY TAMPER PROOF SEALS INSTALLED AND/OR BE APPROVED BY EASTBOUND INTERNATIONAL SPEEDWAY TECH OFFICIALS
- 25.3 SEALED OR APPROVED ENGINES MUST PULL A MINIMUM OF 18 INCHES OF VACUUM (**NO TOLERANCE**)
- 25.4 ALL VACUUM TESTS WILL BE AT 900 RPM USING TRACK TECH TOOLS AND RPM GAUGE ONLY
- 25.5 REPAIRED/FRESHENED CRATE ENGINES WILL HAVE TO MEET SPECIFIC GUIDELINES AS SET BY EASTBOUND INTERNATIONAL SPEEDWAY
- 25.6 THE MANDATORY CARBURETOR IS A **650 CFM 4150 HOLLEY #80541-1**
- 25.7 A **650 CFM 4150 HOLLEY #80541-1** IS TO BE INSTALLED WITH NO MODIFICATIONS "BOX STOCK". THE CARBURETOR WILL BOLT DIRECTLY TO THE INTAKE USING A GASKET ONLY
- 25.8 NO SPACER PLATE WILL BE ALLOWED
- 25.9 TWO THROTTLE RETURN SPRINGS ARE MANDATORY
- 25.10 CARBURETOR SHALL REMAIN AS PRODUCED, WITH THE EXCEPTION OF CHOKE MECHANISM AND EXTERNAL CHOKE HOUSING WHICH CAN BE REMOVED
- 25.11 ALL CRATE ENGINES MUST MEET ORIGINAL SPECIFICATIONS AS PER GM PERFORMANCE THIS INCLUDES ALL VALVE ANGLES AND COMPRESSION
- 25.12 THE 4BBL. OPTION DOES NOT PERMIT THE USE OF ANY PERFORMANCE BUILT, SPECIALITY BUILT OR MODIFIED CARBURETORS OR THEIR COMPONENTS. A 650 CFM 4150 #80541-1 "BOX STOCK" IS THE ONLY APPROVED 4BBL. CARBURETOR AND MUST RETAIN ALL NON-MODIFIED ORIGINAL COMPONENTS TO BE IN COMPLIANCE

- 25.13 INSPECTIONS MAY INCLUDE, CONFIRMATION OF STOCK ORIGINAL COMPONENTS, GAUGE TESTS (GO/NO GO) AS WELL AS ANY OTHER TESTS TO CONFIRM COMPLIANCE
- 25.14 ALL AIR ENTERING THE ENGINE FOR COMBUSTION PURPOSES MUST ENTER THROUGH THE AIR HORN OF THE CARBURETOR

**PLEASE NOTE:**

THERE IS NO TOLERANCE ON THE 18 INCH VACUUM RULE FOR ANY ENGINE VARIATION. ENGINES MUST PRODUCE A **STEADY** 18 PLUS INCHES OF VACUUM. ENGINES WITH ERRATIC READINGS THAT **MOVE BELOW 18 INCHES** OR **ANY AMOUNT LESS THEN 18 INCHES** WILL NOT MEET THE MINIMUM 18 INCH VACUUM REQUIREMENT FOR THE 4BBL OPTION. ALL VACUUM TESTS WILL BE AT 900 RPM USING **TRACK TECH TOOLS AND RPM GAUGE ONLY**. NO TIMING, CARBURETOR, OR OTHER ENGINE ADJUSTMENTS ARE PERMITTED POST RACE OR DURING THE TECH PROCEDURE

**26. EXHAUST**

- 26.1 HEADERS ARE PERMITTED BUT PRIMARY TUBES MUST BE NO LARGER THAN 1 5/8" FOR THE FULL LENGTH OF THE TUBE (FLANGE TO COLLECTOR)
- 26.2 NO STEP TUBES ALLOWED
- 26.3 COLLECTOR MUST BE 3" DIAMETER AND BE SECURED TO THE EXHAUST PIPE (3.5" MAX. DIAMETER)
- 26.4 COLLECTOR IS TO REMAIN STOCK LENGTH
- 26.5 A "Y" PIPE COLLECTOR IS REQUIRED TO ADAPT INTO A SINGLE EXHAUST PIPE.
- 26.6 HEADERS ARE TO BE CONVENTIONAL CROSSOVER DESIGN ONLY (EXAMPLE: SCHOENFELD 135 HEADERS)
- 26.7 NO 180-DEGREE HEADERS PERMITTED
- 26.8 NO STEPPED HEADERS PERMITTED MILD STEEL HEADERS ONLY
- 26.9 NO STAINLESS, CHROME, OR COATED (INSIDE OR OUTSIDE) HEADERS PERMITTED.
- 26.10 A "BLOCK HUGGER" HEADER, WITH MAXIMUM 1 5/8" TUBES AND A 2 1/2" 3-BOLT FLANGE, THAT MEASURES NO MORE THAN 10" TOP TO BOTTOM, WITH A MAXIMUM OUTBOARD MEASUREMENT OF 3 1/4", IS ALLOWED
- 26.11 WHEN INSTALLED, THE HEADER EXHAUST FLANGE MUST NOT BE LOWER THAN THE POINT WHERE THE BLOCK AND OIL PAN BOLT MEET
- 26.12 EXHAUST PIPE OFF THE HEADER MUST BE 2" O.D. EXHAUST TUBING
- 26.13 THE FIRST FOUR INCHES (MAXIMUM) CAN BE USED TO REDUCE THE EXHAUST PIPE OFF THE HEADER TO 2" O.D. MAXIMUM. THE NEXT 2 FEET MUST BE 2" O.D. AFTER WHICH IT CAN GO TO 2 1/2" FOR THE REMAINDER

- OF THE 4 FOOT MINIMUM DESCRIBED ABOVE. THE REST OF THE EXHAUST WILL REMAIN THE SAME AS THE CAST IRON MANIFOLDS.
- 26.14 MAY HAVE A STOCK OEM CAST IRON EXHAUST MANIFOLD WITH A MAXIMUM 2" DIAMETER OUTLET. TWO-INCH EXHAUST PIPE OFF MANIFOLD CAN GO TO 2 ½" I.D. AND MUST REMAIN 2 ½" OR LESS FOR A MINIMUM OF FOUR FEET OR UNTIL IT EXITS. AFTER FOUR FEET, IF DUAL EXHAUST GOES INTO ONE, IT MUST REMAIN AS ONE UNTIL IT EXITS. MAXIMUM INSIDE DIAMETER OF SINGLE TAILPIPE IS 4 INCHES.
  - 26.15 PIPES MUST BE TIGHT AT ALL JOINTS (WELDED OR CLAMPED) AND SECURELY FASTENED. MUFFLERS ARE PERMITTED (STRAIGHT THROUGH ONLY), MUST BE REMOVABLE FOR INSPECTION.
  - 26.16 EXHAUST MUST BE MOUNTED IN SUCH A WAY AS TO DIRECT GASES AWAY FROM THE DRIVER'S COMPARTMENT AND AWAY FROM ANY AREAS OF POSSIBLE FUEL SPILLAGE.
  - 26.17 EXHAUST MUST EXIT OUT THE RIGHT SIDE OF THE CAR JUST AHEAD OF THE REAR WHEEL
  - 26.18 NO ANGLE CUTS OR BALANCE TUBES ARE PERMITTED
  - 26.19 PIPE WRAP RECOMMENDED.
  - 26.20 MANIFOLDS AND HEADERS WILL REMAIN AS PRODUCED
  - 26.21 NO PORTING, POLISHING, ACID TREATING, BLUEPRINTING IS PERMITTED.
  - 26.22 ANY INDICATION OF GRINDER MARKS OR ACID COULD RENDER THE CAR ILLEGAL.
  - 26.23 MANIFOLDS AND HEADERS ARE SUBJECT TO REMOVAL FOR INSPECTION.

## **27. FUEL CELL**

- 27.1 AN APPROVED FUEL CELL (MANDATORY) MUST HAVE REAR HOOP PROTECTION BARS, MIN. 1 3/4" X .095" TUBING, NO LOWER THAN 2" BELOW BOTTOM OF REAR AXLE TUBES
- 27.2 FUEL CELL MUST HAVE A ONE-WAY CHECK VALVE IN THE VENT LINE
- 27.3 NO VENTED GAS CAPS PERMITTED. GAS CAP MUST HAVE AN APPROPRIATE ATTACHING LINE TO PREVENT ITS LOSS
- 27.4 NEOPRENE OR STEEL GAS LINE MUST BE SECURELY FASTENED UNDER THE FLOOR
- 27.5 NO COPPER LINES PERMITTED.
- 27.6 METAL FUEL FILTERS ONLY.
- 27.7 GROUND STRAP ATTACHED TO FILLER NECK TO CHASSIS IS MANDATORY.
- 27.8 MUST HAVE 2 X1/8 SAFETY STRAPS UNDERNEATH CELL.

## 28. WEIGHT

**NOTE: CARS WILL BE WEIGHED POST RACE WITH DRIVER IN THE DRIVER'S SEAT AND INCLUDES ALL DRIVER SAFETY EQUIPMENT**

- 28.1 602 CRATE WITH ORIGINAL SEALS  
2900 POUNDS      18 + VACUUM      4 BBL CARB OPT.
- 28.2 CRATE REPAIRED/FRESHENED - MISSING FACTORY SEALS  
3000 POUNDS      18 + VACUUM      4 BBL CARB OPT.
- 28.3 CRATE FRESHENED - MISSING FACTORY SEALS  
3100 POUNDS      LESS THAN 18 VACUUM      2 BBL CARB
- 28.4 BUILT  
3100 POUNDS      VACUUM N/A      2 BBL CARB
- 28.5 MAXIMUM LEFT SIDE WEIGHT 55%
- 28.6 MAXIMUM REAR WEIGHT 45%
- 28.7 CARS USING A 2 X 3 FRONT CLIP MUST ADD 25 POUNDS OF BALLAST IN FRONT OF THE FIRE WALL (AHEAD OF THE FOOT BOX), SPLIT EQUALLY TO EACH FRAME RAIL. THIS WEIGHT IS PART OF THE TOTAL WEIGHT, NOT IN ADDITION TO TOTAL
- 28.7 NO HYDRAULIC, PNEUMATIC, RATCHET, ELECTRIC, OR ANY OTHER KIND OF MOVEABLE WEIGHT DEVICES ANYWHERE IN OR ON THE CAR
- 28.8 ADDED WEIGHT MUST BE SECURELY FASTENED WITH 2 HALF INCH GRADE 8 BOLTS, PAINTED WHITE AND HAVE CAR NUMBER ON IT
- 28.9 WEIGHT MUST NOT BE BELOW FRAME RAILS
- 28.10 MANAGEMENT MAINTAINS THE RIGHT TO ADJUST OR FURTHER DEFINE THE WEIGHT RULE

## 29. TIRES AND WHEELS

**NOTE: NEW TIRES WILL BE MADE AVAILABLE THROUGH EASTBOUND INTERNATIONAL SPEEDWAY; TIRES HAVE TO BE PURCHASED THROUGH TRACK OR A TRACK AGENT. EASTBOUND INTERNATIONAL SPEEDWAY RESERVES THE RIGHT TO DEFINE TIRE SIZE, STRUCTURE, COMPOUND, ALLOWABLE QUANTITIES AND CHEMICAL TREATMENTS TO ALL COMPETITORS FOR ALL EVENTS. TIRES COULD REQUIRE FURTHER BRANDING BY OFFICIALS BEFORE THEY ARE ELIGIBLE FOR USE.**

- 29.1 TIRES WILL BE HOOSIER 10420 OR 10425



- 29.2 8" TREADED TIRES COMPOUND 890
- 29.3 UP TO A MAXIMUM OF EIGHT (8) TIRES CAN BE REGISTERED PRIOR TO FIRST RACE (EVENT). THIS CAN CONSIST OF UP TO SIX
- 29.4 (6) NEW OR USED PLUS TWO (2) ADDITIONAL USED TIRES. AFTER THAT, ONE (1) EXTRA TIRE, NEW OR USED, CAN BE REGISTERED AFTER RACES (EVENTS) 2, 4, 6, 8, & 9. DAMAGED TIRES CAN BE REPLACED
- 29.5 DAMAGED TIRES MUST BE RETURNED TO TRACK IN ORDER TO REGISTER ANOTHER NEW OR USED TIRE
- 29.6 SERIAL NUMBERS MUST BE LEGIBLE ON USED / DAMAGED TIRES FOR REGISTRATION PURPOSES
- 29.7 NO CHEMICAL TREATING OF TIRES (I.E. COMPOUND ALTERING / TIRE SOFTENING).
- 29.8 STEEL WHEELS ONLY
- 29.9 OVERSIZE STEEL WHEEL NUTS THAT THREAD ALL THE WAY OVER THE STUD REQUIRED
- 29.10 MINIMUM HALF-INCH STUDS RECOMMENDED.
- 29.11 3/8" ROUND STOCK MAY BE USED TO PROTECT RIM LIP
- 29.12 NO OFFSET WHEELS WITH LESS THAN 1" OF OFFSET
- 29.13 NO WHEEL SPACERS ALLOWED ON 1.75" OR LESS OFFSET WHEELS
- 29.14 WHEELS THAT ARE OFFSET 2 INCHES OR MORE MAY USE A ONE- INCH MAXIMUM SPACER. SPACER MUST BE ONE SOLID ALUMINUM PIECE
- 29.15 MAXIMUM OVERALL WIDTH (FRONT AND REAR) SHALL NOT EXCEED 78" FROM OUTSIDE OF ONE WHEEL TO OUTSIDE OF OPPOSITE WHEEL AT SPINDLE HEIGHT
- 29.16 TIRES CANNOT BE MORE THAN 2" OUTSIDE THE BODY.

### **30. SAFETY**

- 30.1 HELMETS MUST BE SNELL 2010 & SA (OR BETTER) APPROVED – **SNELL 2010 & SA HELMETS WILL EXPIRE IN OCTOBER 2021**
- 30.2 FULL FACE HELMETS ARE MANDATORY.
- 30.3 HELMETS MUST BE WORN AT ALL TIMES CAR IS ON TRACK.
- 30.4 SFI RATED HEAD AND NECK RESTRAINT SYSTEMS ARE MANDATORY, SUCH AS HANS OR HUTCHENS ARE RECOMMENDED.
- 30.5 SEAT BELTS MUST BE WORN WHENEVER CAR IS ON THE RACETRACK. BELTS MUST BE IN GOOD CONDITION AND NOT LESS THAN 1-1/2 INCHES WIDE. MANUFACTURER REPLACEMENT TIME FRAME RECOMMENDED – USUALLY 3 YEARS. A MINIMUM FOUR-POINT HARNESS IS MANDATORY. LAP BELTS MUST BE BOLTED TO ORIGINAL SEAT BELT MOUNTS. SHOULDER BELTS MUST BE FASTENED TO THE ROLL BAR AT SHOULDER HEIGHT. ALL BELTS MUST HAVE SEAT BELT MOUNTS AND FASTENERS. NO TYING, RIVETING, OR ANY OTHER METHOD OTHER THAN PROPER ATTACHMENT IS ACCEPTABLE.
- 30.6 MUST WEAR A SFI RATED FIRE SUIT WHENEVER CAR IS ON THE TRACK. IF SUIT HAPPENS TO BE TWO PIECE, BOTH THE TOP AND BOTTOM MUST BE WORN AT THE SAME TIME
- 30.7 FIRE RETARDANT RACING GLOVES AND RACING SHOES ARE MANDATORY

- 30.8 HELMET, SFI RATED HEAD AND NECK RESTRAINT, GLOVES AND SHOES MUST ACCOMPANY VEHICLE AT TIME OF INSPECTION FOR ALL COMPETITORS
- 30.9 A SECURELY FASTENED, QUICK RELEASE FIRE EXTINGUISHER IS REQUIRED
- 30.10 WITHIN EASY REACH OF THE DRIVER WITH A RECHARGE SLIP DATED NO EARLIER THAN JANUARY FIRST OF THE CURRENT YEAR
- 30.11 DRIVER'S SIDE WINDOW NET (QUICK RELEASE, PROPERLY WORKING TOP LATCH) IS REQUIRED
- 30.12 SAFETY APPROVED FUEL CELLS ARE MANDATORY
- 30.13 BATTERIES MUST BE SECURELY MOUNTED AND SHIELDED
- 30.14 LOOSE OBJECTS AND/OR WEIGHTS WILL NOT BE ALLOWED IN DRIVER'S COMPARTMENT (BETWEEN FRONT AND REAR HOOP)
- 30.15 ANY OTHER WEIGHT ADDED MUST BE SECURELY MOUNTED; A MINIMUM OF TWO HALF-INCH BOLTS USED WITH EACH WEIGHT. WEIGHTS MUST BE PAINTED WHITE. CAR NUMBER SHOULD BE ON ALL WEIGHTS
- 30.16 DRIVE SHAFT HOOP REQUIRED TOWARD FRONT OF DRIVE SHAFT. HOOP MUST BE CONSTRUCTED OF MATERIAL SUFFICIENT TO CONTAIN THE DRIVE SHAFT IN THE EVENT OF U-JOINT/DRIVE SHAFT FAILURE. DRIVE SHAFT MUST BE PAINTED WHITE
- 30.17 ROLL BAR PADDING IS RECOMMENDED AROUND DRIVER.

### **31. BODIES, INTERIORS AND AIR DAMS**

- 31.1 NORTH AMERICAN MID OR FULL SIZE STEEL BODIED SEDANS OR KIT \ BODIES (STEEL, FIBERGLASS OR ALUMINUM)
- 31.2 NO STATION WAGONS, TRUCKS, PANELS, VANS, OR CONVERTIBLES
- 31.3 BODIES MUST BE SAME AS AVAILABLE FROM FIVE-STAR.
- 31.4 BODIES MUST BE EASILY IDENTIFIED AND BE ENTIRELY FROM ONE MODEL (I.E.: MONTE CARLO SNOUT, HOOD, ROOF, REAR QUARTERS AND REAR BUMPER COVER)
- 31.5 ALL BODIES SHOULD CONFORM TO "FIVE-STAR SHORT TRACK TEMPLATE" DIMENSIONS AND ANGLES, AND MAY BE REQUIRED TO FIT TEMPLATES. (NO DIRT STYLE FRONT OR REAR BUMPER COVERS).
- 31.6 NO CUSTOM DESIGNED BODIES
- 31.7 NO OUTLAW EXTENDED QUARTER PANELS AND DECK LIDS
- 31.8 NO HIGH DOWN FORCE BODIES
- 31.9 NO CARBON FIBER BODY PARTS.
- 31.10 FRONT FENDERS AND TOP OF WINDSHIELD MUST BE KEPT FREE FOR CONTINGENCY DECALS
- 31.11 ALUMINUM, FIBERGLASS OR STEEL AFTERMARKET BODIES O.K. WITH RUBBER FRONT AND REAR BUMPERS.
- 31.12 TRUNK LID (MINIMUM 3 SQ. FT. OPENING WITH 12" MIN. MEASURE EITHER WAY) MUST BE FUNCTIONAL
- 31.13 SAFETY RETAINERS REQUIRED ON HOOD AND TRUNK LIDS
- 31.14 TRUNK LID MAY NOT BE DISHED.
- 31.15 NO CUT DOWN DOORS

- 31.16 DOOR LENGTH AND SHELF WIDTH MUST MEET FIVE-STAR SPECIFICATIONS. SHELF WIDTH MAXIMUM 2" LEFT, 3.5" RIGHT.
- 31.17 BODY MUST BE CENTERED ON FRAME AND RETAIN ITS STOCK APPEARANCE, DIMENSIONS AND ANGLES.
- 31.18 PASSENGER SIDE WINDOW MUST REMAIN COMPLETELY OPEN
- 31.19 A VENT WINDOW TO ACCOMMODATE AN AIR DUCT CAN BE INSTALLED BACK FROM THE BOTTOM OF THE WINDSHIELD PILLAR A MAXIMUM OF 10½" AND UP AT 90 DEGREES FROM THE EDGE OF DOOR.
- 31.20 REAR DECK SPOILER (FIVE-STAR TYPE) ALLOWED. MAXIMUM LENGTH OF 60" AND A MAXIMUM HEIGHT OF 5", MEASURED ACROSS THE BACK. NO BOXING. SPOILER MUST BE CENTERED SIDE TO SIDE ON REAR DECK
- 31.21 REAR DECK HEIGHT MAY BE A MAXIMUM OF 34.5" OFF THE GROUND.
- 31.22 NO ADJUSTABLE REAR QUARTER PANELS.
- 31.23 FULL FRONT WINDSHIELD REQUIRED. MUST BE LEXAN OR APPROVED SAFETY GLASS. TOP OF FRONT WINDSHIELD MUST REMAIN AVAILABLE FOR DIVISION SPONSOR
- 31.24 LEXAN REAR WINDOW AND QUARTER WINDOWS ALLOWED. BACK WINDOWS MUST BE SECURELY BRACED INTERNALLY TO PREVENT SIGNIFICANT BOWING AT RACING SPEEDS (SEE SUCKED DOWN ROOF AND REAR WINDOW RULE BELOW)
- 31.25 ALL WINDOW PILLARS SHOULD BE IN PLACE. PAINTED ROLL BARS ARE NOT AN ACCEPTABLE SUBSTITUTE. NO ADDITIONAL MATERIAL MAY BE ADDED IN PILLAR AREA.
- 31.26 MUST HAVE ORIGINAL GRILLE OR BE MESHED IN
- 31.27 BODY MUST BE A MINIMUM OF 4" FROM THE GROUND AT ALL POINTS.
- 31.28 MUST HAVE FULL STEEL (MIN .032" THICKNESS) OR ALUMINUM (MIN.040" THICKNESS) INTERIOR
- 31.29 COMPLETE STEEL FIREWALL (FRONT AND REAR), FLOORBOARDS, AND AREA SURROUNDING DRIVER ARE MANDATORY
- 31.30 A STEEL PLATE UNDER THE DRIVER'S FEET AND SEAT IS STRONGLY RECOMMENDED
- 31.31 AFTERMARKET RUBBER NOSE CONE MUST MATCH THE BODY
- 31.32 REAR BUMPER COVER MUST MATCH BODY
- 31.33 REAR BUMPER COVERS MAY NOT BE TRIMMED, HULLED, DRILLED, OR OTHERWISE CHANGED OR MODIFIED
- 31.34 NO WINGS OR GROUND EFFECTS ANYWHERE INSIDE OR OUTSIDE OF CAR
- 31.35 THE INTERIOR OF THE CAR CANNOT BE ARRANGED IN SUCH A WAY TO LOOK LIKE A SPOILER.
- 31.36 RIGHT SIDE FLOOR PAN MAY BE LEVEL WITH TRANSMISSION HEIGHT, ANGLE UP TO BOTTOM OF THE PASSENGER SIDE WINDOW OPENING, OR DROP BACK DOWN WITH LEVEL OF FLOOR ON DRIVER'S SIDE.
- 31.37 NO HOLES ALLOWED IN HOOD OR OTHER BODY PANELS OTHER THAN STOCK HOLES
- 31.38 NO COWL INDUCTION
- 31.39 ANY RADIATOR DUCT MUST NOT EXTEND AHEAD OF THE FRONT BUMPER OR BEHIND THE RADIATOR AND MUST BE AT LEAST 4" OFF THE GROUND

- 31.40 ALL CARS IN COMPETITION MUST HAVE A COMPLETE PAINT JOB OR VINYL WRAP. PRIMER IS NOT CONSIDERED PAINT.
- 31.41 NO BODY MODIFICATIONS ALLOWED. ANY BODIES THAT APPEAR TO BE MOUNTED IN A MANNER THAT COULD PUT MORE AIR ON THE REAR SPOILER (SUCKED DOWN REAR ROOF AND/OR WINDOW) OR THE FRONT AREA OF THE CAR COULD BE REQUIRED TO MAKE CHANGES SUCH AS TRIMMING OR REMOVING REAR SPOILER, REMOVING HOOD OR OTHER ADJUSTMENTS TO COMPENSATE FOR ANY POSSIBLE ADVANTAGE IN THE OPINION OF THE TRACK OFFICIALS
- 31.42 ALL CARS MUST BEGIN EACH RACE MEET WITH COMPLETE BODY UNLESS DAMAGED IN PRACTICE AND/OR OK'D BY TRACK OFFICIALS

### **32. MEASUREMENTS**

- 32.1 ALL HEIGHTS WILL BE MEASURED WITH DRIVER IN THE CAR
- 32.2 MINIMUM ROLL CAGE HEIGHT TO BE 39" FROM BOTTOM OF FRAME
- 32.3 MINIMUM HEIGHT OF DOOR BARS TO BE 22 ½" FROM BOTTOM OF FRAME
- 32.4 MINIMUM 5" RIDE HEIGHT MEASURED AT SIDE FRAME RAILS
- 32.5 MINIMUM CRANKSHAFT HEIGHT TO BE MINIMUM FRAME HEIGHT PLUS 7"
- 32.6 48" ROOF HEIGHT (2002 OR NEWER BODY 47") MEASURED BACK FROM THE WINDSHIELD TO THE GROUND PER FIVE STAR SPECIFICATIONS
- 32.7 ROOF HEIGHT AT TOP EDGE OF REAR WINDOW SHOULD BE NO MORE THAN 1.5" LOWER THAN ROOF HEIGHT AT FRONT (10INCHES BACK FROM WINDSHIELD)
- 32.8 TOP OF REAR QUARTERS SHOULD NOT BE TRIMMED TO ALLOW SIDES OF ROOF TO BE LOWERED.
- 32.9 REAR DECK HEIGHT AND SPOILER HEIGHT COULD BE RELATIVE TO ANY COMBINATION OF DECK LENGTH, ROOF HEIGHT, NOSE HEIGHT AND ANGLE, FRONT FENDER CONTOUR, WINDSHIELD ANGLE, DOOR LENGTH AND WIDTH
- 32.10 REAR DECK HEIGHT MAY BE A MAXIMUM OF 34.5" OFF THE GROUND. REAR DECK LENGTH WILL CONFORM TO FIVE STAR SPECIFICATIONS REMAINING MEASUREMENTS MUST CONFORM TO FIVE STAR SPECIFICATIONS
- 32.11 MINIMUM GROUND CLEARANCE OF ANY BODY COMPONENT IS 4" INCLUDING BUMPER, BUMPER COVERS, AND SIDE SKIRTS.

### **33. RUB RAILS**

- 33.1 A SINGLE EXTERIOR RUB RAIL MAY BE USED ON EACH SIDE OF THE CAR, FROM BEHIND THE FRONT WHEEL PARALLEL TO THE GROUND, TO AHEAD OF THE REAR WHEEL, BREAK FOR THE REAR WHEEL OPENING AND CONTINUE TOWARD THE REAR OF THE CAR AND FASTEN TO THE REAR BUMPER
- 33.2 SQUARE OR RECTANGULAR TUBING OR ROUND PIPE ONLY. MAXIMUM 1" O.D. OR ½" BY 2" O.D
- 33.3 NO EXPOSED BOLT HEADS

- 33.4 FRONT AND REAR ENDS WILL TAPER AT 45 DEGREES AND BE CLOSED IN. BOLT HEADS MUST BE COUNTERSUNK
- 33.5 RECOMMEND A ¼" X 2" ALUMINUM FLAT BAR WITH TAPERED ENDS
- 33.6 NO SHARP EDGES. RUB RAILS MUST FIT TIGHT WITH SIDE OF CAR (BOLTED TIGHTLY TO OUTSIDE DOOR BAR WITHIN 8" OF EITHER END AS WELL AS ALONG THE LENGTH) AND BLEND WITH CAR COLORS
- 33.7 NUMBERS AND LETTERING MUST BE OVER RUB RAILS.

#### **34. BUMPERS**

- 34.1 BUMPERS MUST BE USED FRONT AND REAR
- 34.2 THE CENTER OF THE FRONT BUMPER MUST MEASURE BETWEEN 15" AND 17" FROM THE GROUND
- 34.3 BUMPERS WILL BE CONSTRUCTED OF MAXIMUM 2" TUBING, AND SHALL NOT HAVE ANY SHARP EDGES EXPOSED
- 34.4 MUFFLER PIPE OR .065 STEEL ONLY.
- 34.5 REAR BUMPER AND BRACE BARS MUST BE SUFFICIENT TO PROTECT FUEL CELL OR TANK
- 34.6 A CABLE OR CHAIN OF SUFFICIENT STRENGTH TO LIFT CAR MUST BE EXPOSED IN CENTER OF FRONT AND REAR BUMPERS TO ALLOW FOR QUICK PICK- UP
- 34.7 CARS WITH HINGED TRUNK LIDS AND HOODS ARE EXEMPT
- 34.8 A MINIMUM OF 12" IS MANDATORY FOR FRONT CRUSH ZONE, NO BRACING OF THE BUMPERS WILL BE ALLOWED IN THIS AREA.
- 34.9 A MINIMUM OF 8" IS MANDATORY FOR REAR CRUSH ZONE, NO BRACING WILL BE ALLOWED IN THIS AREA.
- 34.10 ALL BUMPERS MAY BE DRILLED FOR TESTING AND ONLY ACCEPTABLE THICKNESS WILL BE PERMITTED.

#### **35. PAINT AND NUMBERS**

- 35.1 ALL CARS MUST HAVE THEIR ASSIGNED NUMBERS ON BOTH SIDES OF THE CAR AND ON THE ROOF (READABLE FROM THE GRANDSTANDS) AT LEAST 20" HIGH AND 4" THICK IN A COLOR THAT CONTRASTS WITH THE CAR COLOR
- 35.2 A 6" WHITE NUMBER MUST BE ON THE TOP RIGHT FRONT WINDSHIELD. NO GRAY, SILVER, GOLD, METAL FLAKE OR TRICK NUMBERS
- 35.3 NUMBERS DEEMED DIFFICULT TO SCORE, THE DRIVER WILL BE NOTIFIED AND ANY SCORING PROTESTS BY THAT DRIVER WILL NOT BE ACKNOWLEDGED
- 35.4 FRONT AND REAR SNOUTS SHOULD BE PAINTED THE SAME COLOR AS THE CAR.
- 35.5 ANYONE REQUESTING A CAR NUMBER MUST EMAIL BOB@EASTBOUNDPARK.COM

### **36. LISTENING DEVICES**

- 36.1 RACECEIVER OR SCANNER IS MANDATORY. IF USING A SCANNER, IT MUST BE MOUNTED IN A SECURE LOCATION OUTSIDE OF DRIVER'S REACH. ONLY THE TRACK FREQUENCY 454.0000 MHZ. IS TO BE PROGRAMMED
- 36.2 SCANNERS WILL BE SUBJECT TO INSPECTION FOR OTHER FREQUENCIES
- 36.3 RACECEIVER CHANNEL IS 000 (THE DEFAULT CHANNEL)
- 26.4 2 WAY RADIOS WILL BE ALLOWED. FREQUENCY MUST BE PROVIDED TO OFFICIALS AND YOU MUST HAVE EITHER YOU OR YOUR SPOTTER MONITORING TRACK FREQUENCY AT ALL TIMES DURING ON TRACK ACTIVITIES
- 36.5 NO OTHER ELECTRONIC COMMUNICATION DEVICES ALLOWED SUCH AS CELLULAR TELEPHONES.

### **37. MISCELLANEOUS**

- 37.1 ONE INSIDE MIRROR MAY BE USED AND MUST BE MOUNTED INSIDE CAR
- 37.2 ONE LEFT SIDE MIRROR, MAXIMUM WIDTH OF 4" AT ANY GIVEN POINT, NOT TO EXTEND BEYOND BODY
- 37.3 ANYTHING NOT SPECIFIED AS ALLOWED MUST BE STOCK
- 37.4 ANY MISINTERPRETATION OF THE RULES WILL BE SUBJECT TO A FINAL DECISION BY TRACK OFFICIALS. TRACK OFFICIALS MAY CHECK ANY CAR AT ANY TIME
- 37.5 PREVIOUSLY RACED SPORTSMAN CARS WITH BODIES OF EARLIER VINTAGE THAN FIVE-STAR CATALOG MAY BE ALLOWED.
- 37.6 TOWING POINTS MUST BE AVAILABLE ON FRONT AND REAR FRAME
- 37.7 EASTBOUND SPEEDWAY RESERVES THE RIGHT TO CONFISCATE AND RETAIN ANY PARTS OR COMPONENTS THAT ARE DEEMED TO BE NON-CONFORMING TO THE RULES SET FORTH IN THESE PAGES
- 37.8 THE DECISION OF TRACK MANAGEMENT WILL BE FINAL.

CONTACT INFO:

GENERAL INQUIRES – BOB SMITH – [BOB@EASTBOUNDPARK.COM](mailto:BOB@EASTBOUNDPARK.COM)

TECHNICAL INQUIRES – GERARD RONAYNE – [GRCHEVY@HOTMAIL.COM](mailto:GRCHEVY@HOTMAIL.COM)