



# 2026 ENDURO RULES

## DRIVER ELIGIBILITY

Drivers must be a minimum of 16 years of age with a valid driver's license to compete in Enduro racing.

All drivers under 18 must have parental/legal guardian consent, in writing.

Drivers under 18 must use an approved Head/Neck Restraint system. Email [tech@eastboundpark.com](mailto:tech@eastboundpark.com) for approval

All drivers should have a government-issued photo ID with them at the event; if requested and not available, they will not be permitted to race.

All competitors and pit crew members will be required to complete waivers before entering the pit/infield area of the Tracks. Drivers suspected of being impaired by any substance will not be allowed to participate and will be asked to leave the pit/infield area.

## Vehicle Selection

1. Any uni-body 4 or 6-cylinder, naturally aspirated, non-VTEC (i-VTEC allowed); car, van, or SUV with a maximum 122" inch wheelbase. (No Trucks)
  - a. No convertibles, hybrid, hybrid electric, T-tops, mid-engine, aluminum-bodied, special production/sports edition, and/or full-frame vehicles. Sunroofs must have glass removed and be covered with a steel plate, securely fastened on the outside.
  - b. Front or rear-wheel drive, automatic or standard transmissions allowed.
  - c. Complete stock body, frame(s), and suspension must be retained with readable VIN/serial numbers.
  - d. All glass, lights, mirrors, carpet, and loose trim must be removed except the windshield. No sealing or resizing of window openings. Factory dash and rearview mirror can remain.
  - e. Airbags must be removed.
  - f. Doors must be welded or bolted closed.
  - g. Stock bumpers and covers must remain. Tow hooks required, front and rear, minimum – loop of chain.
  - h. Any car deemed not structurally sound (including but not limited to rust) or outside the intentions of the division will be disallowed at the sole discretion of track officials. If you have any questions, ask before wasting time and money.

## DRIVER PROTECTION & SAFETY EQUIPMENT

1. Driver Protection
  - a. Full-face helmet (Snell 2010 or newer) is mandatory.
  - b. Long sleeve shirt, denim-style long pants, or fire retardant coveralls are mandatory; an SFI-rated single or double-layer driver suit is recommended.
  - c. No open-toed or open-heel footwear. SFI racing shoes are recommended.
2. Safety Equipment
  - a. Driver Safety Belts - Minimum 4-point harness with 3" belts. They must be in good condition and dated within the last five years.
  - b. Fire Extinguisher - Minimum 2.5 lb. quick-release fully, securely mounted with a metal bracket and a current recharge slip (dated after January 1 of the current year). Must be mounted within reach of the driver.
  - c. Seat - Stock seats may be replaced with a seat from another make/model or an aluminum seat but it must remain on the tracks; no fiberglass seats.
  - d. Window Net - Must have a driver's side window net with a top latch release, mounted within reach of the driver.
  - e. Roll Bar
    - i) Minimum single hoop, "H" style roll bar, the roll bar will run from the floor vertically at the "B" pillar with a minimum of 0.95" tubing. It must include a crossbar welded at shoulder height, 12" square plate (minimum four bolts) attaching to the roof and two 8" square plates (minimum four bolts each) attaching to the floor. Full roll cages are recommended.
  - f. Door Plate - Minimum 3/16" steel door plate required, bolted with at least eight (8) 3/8" grade 8 bolts, with washers and lock nuts. No blunt or sharp edges. The plate must be fastened inside and be a minimum size of 4" from the front and rear wheels and 12" high, placed in the center of the door as measured from top to bottom.
  - g. **All cars must be equipped with a grade 70 chain or minimum 3/8"- inch chain on front and rear of car formed into a loop large enough for a tow truck hook. The chain must be securely mounted and accessible from the outside of the car, or at most by opening the hood. If the safety chain is NOT easily accessible, officials reserve the right to hook the car in any manner deemed necessary and will not be held responsible for any resulting damage.**

## ENGINE, TRANSMISSION, FUEL & ELECTRICAL SYSTEM

1. Engine
  - a. Maximum size is 3.6L. Stock engines only with factory spec ECU. No reprogrammed, chipped, or modified ECU's.
  - b. Stock intake and air filter required; must be functional with cover.
  - c. Exhaust – Must be single exhaust, max 2.5" pipe, can exit out of the side; it must extend past the driver and point away from the fuel tank.
2. Radiator
  - a. One radiator, mounted in stock location.
  - b. Radiator overflow must exit within the engine bay
  - c. Water only; no antifreeze or additives.
3. Fuel/Fuel Tank
  - a. Maximum octane is 91.
  - b. Stock fuel tank required. A safety chain must be installed under the fuel tank in case of strap failure.
  - c. Fuel lines must run under the floor, not through the driver's compartment.
4. Transmission
  - i) Automatic – Maximum 5 forward gears, 1 reverse.
  - ii) Standard – Maximum 6 forward gears, 1 reverse;
5. Clutch and Flywheel – Must be stock; no lightweight or performance versions.
6. Gears – No aftermarket gear sets, final drives, or custom transmission internals.
7. Aftermarket transmission coolers are allowed; must be securely mounted to the radiator assembly.
8. Battery – Must remain in stock location.
  - a. Factory trunk-mounted batteries require additional brackets/bracing and a metal firewall over the rear seat area.
  - b. Working charging system required; vehicle must start without assistance.

## **SUSPENSION, BRAKES, WHEELS & TIRES**

1. Suspension – All suspension parts must be stock; no modifications.
2. Brakes – Four (4) working brakes are required; stock components only.
3. ABS and Traction/Stability Control Systems – Must be disabled.
4. Wheels
  - a. Maximum 17”.
  - b. OEM or equivalent wheels only, factory offset for make and model, steel or aluminum; no racing wheels.
  - c. All 4 wheels must be the same.
5. Tires
  - a. All tires must be the same size indicated on the door post or equivalent rotational diameter
  - b. Used DOT P-series tires only; no racing or performance tires.
  - c. Maximum speed rating: V.
  - d. Tire tread must measure a minimum 2/32 as measured at three spots on the tire – inside, center, and outside.
  - e. Camber is expected to be stock.

## **WEIGHT & NUMBERS**

1. Weight - No added weight or ballast.
2. Car Numbers
  - a. Must have the car number on both sides of the car, and on the roof, readable from the grandstand (top of number on driver side of roof, bottom on the passenger side).
  - b. Door numbers must be at least 24” high; the car must have a 6” number on the top right of the windshield.
  - c. Numbers must be clearly readable. No gray, silver, gold, metallic, or trick materials. Illegible numbers will result in a) may need to be replaced pre-race, or be ineligible to race, or b) scoring protests not being acknowledged.

## **SCORING & LISTENING DEVICES**

1. Listening Devices - No radio communication allowed.
2. Each car must provide a person to score their car during the race. They must have a smartphone pre-loaded with the Race Clocker app and be at the event in time for the Scorer’s meeting.

## **DISQUALIFICATION**

Any car disqualified (DQ) from the event is not entitled to winnings or any compensation for costs incurred for the event.

## **INTERPRETATION**

Interpretation of these rules is solely at the discretion of Track officials. The Tracks reserve the right to impound non-complying components without compensation to the owner(s). Noncompliance with the specifications herein may result in disqualification, loss of points and winnings/awards, and/or fines. The Tracks are not liable for costs and/or component replacement associated with the inspection process of any race car.